

■ JFSO型 標準仕様表

型 式	吸込 口径 mm	吐出し 口径 mm	60Hz				1750min ⁻¹				50Hz				1450min ⁻¹			
			電動機 kW	揚水量 m ³ /min	全揚程 m	揚水量 m ³ /min	全揚程 m	揚水量 m ³ /min	全揚程 m	電動機 kW	揚水量 m ³ /min	全揚程 m	揚水量 m ³ /min	全揚程 m	揚水量 m ³ /min	全揚程 m		
JFSO-43C	40	32	0.4	0.06	8.4	0.12	6.8	0.18	5.2	—	—	—	—	—	—			
JFSO-43D	40	32	0.75	0.06	11.5	0.12	10.4	0.18	8.8	0.4	0.04	8	0.1	6.8	0.15	5.5		
			1.5	0.06	19.2	0.12	18	0.18	16.6	0.75	0.04	12.5	0.1	11.4	0.15	10		
JFSO-54C	50	40	0.75	0.12	10	0.25	7.3	0.30	5.6	0.4	0.1	6.4	0.2	4.5	0.25	3.2		
			1.5	0.12	13.2	0.25	11.4	0.32	9.5	0.75	0.1	9	0.2	7.8	0.3	5.6		
JFSO-54E	50	40	2.2	0.12	19.5	0.25	16.5	0.32	14	1.5	0.1	14.6	0.2	12.8	0.3	10.8		
			—	—	—	—	—	—	—	—	2.2	0.1	18.5	0.2	16.5	0.3	15	
JFSO-65CX	65	50	1.5	0.2	14.5	0.4	9.7	0.55	5.5	0.75	0.2	8	0.3	6.5	0.4	4.7		
JFSO-65D	65	50	2.2	0.25	15.5	0.5	13	0.7	9	1.5	0.2	11	0.4	9.8	0.6	6.8		
			3.7	0.25	21	0.5	18.5	0.7	15.5	2.2	0.2	15	0.4	13.3	0.6	10.2		
JFSO-65E	65	50	5.5	0.25	26	0.5	22	0.7	18	3.7	0.2	18.5	0.4	15.5	0.6	11.5		
JFSO-86CX	80	65	2.2	0.45	13.2	0.75	11	0.9	8	1.5	0.4	10	0.6	8.6	0.8	6		
JFSO-86D	80	65	3.7	0.45	18.5	0.7	16	1	10	2.2	0.4	13	0.6	11	0.8	7.5		
			5.5	0.45	24	0.7	21.5	1	15	3.7	0.4	17	0.6	15	0.8	12.5		
JFSO-86E	80	65	7.5	0.45	27	0.9	23.5	1.4	16	5.5	0.4	19	0.8	16	1.2	11		
JFSO-86F	80	65	11	0.45	32.5	0.9	29.5	1.4	23.5	7.5	0.4	26.5	0.8	23.5	1.2	19		
			15	0.45	42.5	0.9	39	1.4	33	11	0.4	31	0.8	28.5	1.2	24		
JFSO-108CX	100	80	3.7	0.8	13	1.2	11.4	1.5	8.5	2.2	0.6	9.5	1	8	1.3	5.4		
JFSO-108D	100	80	5.5	0.8	14.4	1.6	12.3	2.2	8.5	—	—	—	—	—	—	—		
			7.5	0.8	17.2	1.6	15	2.2	11	3.7	0.7	11	1.3	9.5	1.8	7		
JFSO-108E	100	80	11	0.8	24.5	1.6	22	2.4	16.5	5.5	0.7	15.3	1.3	13.5	2	9.8		
			15	0.8	30	1.6	27	2.4	21.5	7.5	0.7	19	1.3	17.5	2	14		
JFSO-108F	100	80	18.5	0.8	36.5	1.6	33.5	2.4	28	11	0.7	25.5	1.3	23.5	2	19.5		
			22	0.8	41.5	1.6	38	2.4	32	15	0.7	32	1.3	29.5	2	26		
JFSO-1210E	125	100	7.5	1.3	16.2	2.5	11.5	3.2	8	5.5	1	13.5	2	11	2.8	7		
			11	1.3	21.5	2.5	18	3.4	12.5	7.5	1	16.2	2	13.5	3	9.2		
			15	1.3	25.5	2.5	22.5	3.4	18.5	11	1	21.2	2	18.8	3	14.2		
JFSO-1210F	125	100	18.5	1.3	33	2.5	27	3.4	20	15	1	29.5	2	25	3	19		
			22	1.3	37.5	2.5	31.5	3.4	24.5	—	—	—	—	—	—	—		
			30	1.3	42.5	2.5	36	3.4	28.5	—	—	—	—	—	—	—		
JFSO-1512E	150	125	18.5	2	25.5	4	19	5.7	10	11	1.7	17	3.2	14	4.8	6.8		
			22	2	28	4	21.5	5.7	11.5	15	1.7	20	3.2	17	4.8	9.7		
			30	2	29.5	4	24.5	5.7	14	—	—	—	—	—	—	—		
JFSO-1512F	150	125	30	2	36.5	4	30	5.9	15	18.5	1.7	27	3.2	24	5	13.5		
			37	2	42.5	4	36.5	5.9	23	22	1.7	29	3.2	26	5	14.5		

注1. テスト液は清水です。

注2. 型式末尾の記号によりポンプ形状が変わります。