

SLJ形樹脂製ローラコンベヤ



ローラ	ABS樹脂 30×2.0t
シャフト	アルミ 8丸棒
フレーム	アルミ 63×25×3.0
許容負荷ローラ1本当り	
ローラ幅 (cm)	25 30 40 50 60
許容負荷 (kg)	8 8 8 7 7

LLJ形樹脂製ローラコンベヤ



ローラ	ABS樹脂 38×2.0t
シャフト	アルミ 8丸棒
フレーム	アルミ 63×25×3.0
許容負荷ローラ1本当り	
ローラ幅 (cm)	25 30 40 50 60
許容負荷 (kg)	10 10 10 8 6

SLJ形 30×2.0t× 8丸棒)価格

ピッチ (mm)	機幅 (cm)		25	30	40	50	60
	機長 (m)	機幅 (cm)					
50	1.5	72,000	75,000	86,000	92,000	101,000	
	2.0	93,000	98,000	112,000	120,000	132,000	
	3.0	136,000	141,000	163,000	174,000	194,000	
	90°	101,000	104,000	116,000	122,000	133,000	
75	1.5	54,000	56,000	63,000	68,000	75,000	
	2.0	68,000	70,000	81,000	85,000	94,000	
	3.0	99,000	104,000	117,000	125,000	139,000	
	90°	79,000	82,000	90,000	94,000	102,000	
100	1.5	45,000	47,000	52,000	55,000	61,000	
	2.0	56,000	59,000	67,000	71,000	78,000	
	3.0	81,000	84,000	95,000	101,000	113,000	
	90°	74,000	76,000	84,000	87,000	94,000	

LLJ形 38×2.0t× 8丸棒)価格

ピッチ (mm)	機幅 (cm)		25	30	40	50	60
	機長 (m)	機幅 (cm)					
50	1.5	79,000	84,000	95,000	104,000	113,000	
	2.0	104,000	109,000	124,000	135,000	147,000	
	3.0	151,000	160,000	182,000	198,000	216,000	
	90°	107,000	112,000	124,000	132,000	143,000	
75	1.5	59,000	62,000	69,000	75,000	82,000	
	2.0	74,000	78,000	87,000	95,000	104,000	
	3.0	108,000	115,000	130,000	141,000	154,000	
	90°	84,000	87,000	95,000	102,000	109,000	
100	1.5	48,000	51,000	56,000	61,000	66,000	
	2.0	61,000	64,000	72,000	78,000	85,000	
	3.0	87,000	93,000	105,000	113,000	123,000	
	90°	77,000	81,000	87,000	93,000	100,000	

RLJ形樹脂製ローラコンベヤ



ローラ	ABS樹脂 42×2.5t
シャフト	アルミ 8丸棒
フレーム	アルミ 63×25×3.0
許容負荷ローラ1本当り	
ローラ幅 (cm)	25 30 40 50 60
許容負荷 (kg)	13 13 13 12 9

RLJ形 42×2.5t× 8丸棒)価格

ピッチ (mm)	機幅 (cm)		25	30	40	50
	機長 (m)	機幅 (cm)				
50	1.5	99,000	100,000	108,000	116,000	
	2.0	129,000	131,000	140,000	153,000	
	3.0	189,000	192,000	207,000	224,000	
	90°					
75	1.5	71,000	72,000	78,000	84,000	
	2.0	90,000	92,000	99,000	106,000	
	3.0	133,000	137,000	147,000	159,000	
	90°	97,000	99,000	105,000	112,000	
100	1.5	58,000	59,000	63,000	68,000	
	2.0	74,000	75,000	81,000	86,000	
	3.0	107,000	109,000	117,000	127,000	
	90°	89,000	91,000	95,000	101,000	

NEJ形樹脂製ローラコンベヤ



ローラ	ABS樹脂 50×3.5t
シャフト	アルミ 12パイプ
フレーム	アルミ 63×25×3.0
許容負荷ローラ1本当り	
ローラ幅 (cm)	30 40
許容負荷 (kg)	16 16

NEJ形 50×3.5t× 12パイプ)価格

ピッチ (mm)	機幅 (cm)		30	40
	機長 (m)	機幅 (cm)		
75	1.5	81,000	87,000	
	2.0	102,000	112,000	
	3.0	152,000	167,000	
	90°	110,000	118,000	
100	1.5	66,000	71,000	
	2.0	84,000	91,000	
	3.0	121,000	132,000	
	90°	100,000	108,000	
150	1.5	49,000	54,000	
	2.0	62,000	68,000	
	3.0	90,000	98,000	
	90°	76,000	81,000	

BPJ形樹脂製ローラコンベヤ




ローラ	ABS樹脂 50×3.5t
シャフト	アルミ 12パイプ
フレーム	アルミ 63×25×3.0
許容負荷ローラ1本当り	
ローラ幅 (cm)	30 40 50 60
許容負荷 (kg)	16 16 13 13

BPJ形 50×3.5t× 12パイプ)価格

ピッチ (mm)	機幅 (cm)		30	40	50	60
	機長 (m)	機幅 (cm)				
75	1.5	81,000	91,000	108,000	128,000	
	2.0	102,000	115,000	138,000	163,000	
	3.0	153,000	173,000	207,000	246,000	
	90°	107,000	118,000	138,000	160,000	
100	1.5	64,000	72,000	85,000	100,000	
	2.0	83,000	93,000	112,000	131,000	
	3.0	121,000	136,000	162,000	192,000	
	90°	98,000	107,000	124,000	144,000	
150	1.5	48,000	54,000	63,000	74,000	
	2.0	61,000	67,000	78,000	93,000	
	3.0	90,000	99,000	117,000	138,000	
	90°	72,000	78,000	89,000	100,000	

BUJ形樹脂製ローラコンベヤ



ローラ	ABS樹脂 50×3.5t
シャフト	ステンレス 12パイプ
フレーム	ステンレス 60×30×2.0
許容負荷ローラ1本当り	
ローラ幅 (cm)	30 40 50 60
許容負荷 (kg)	16 16 13 13

BUJ形 50×3.5t× 12パイプ)価格

ピッチ (mm)	機幅 (cm)		30	40	50	60
	機長 (m)	機幅 (cm)				
75	1.5	106,000	120,000	139,000	163,000	
	2.0	135,000	152,000	177,000	207,000	
	3.0	199,000	225,000	265,000	311,000	
	90°	143,000	158,000	179,000	205,000	
100	1.5	87,000	98,000	113,000	131,000	
	2.0	112,000	124,000	145,000	168,000	
	3.0	152,000	181,000	210,000	245,000	
	90°	131,000	144,000	163,000	185,000	
150	1.5	68,000	75,000	85,000	98,000	
	2.0	84,000	93,000	107,000	122,000	
	3.0	123,000	137,000	156,000	181,000	
	90°	101,000	108,000	120,000	133,000	

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境